CARE BETTER, SMILE BRIGHTER IMPROVE WORKING LIFE OF YOUR HANDPIECE THROUGH EFFICIENT CLEANING AND LUBRICATION IN A PLEASED WAY.



Lubrication Unit





TTCARE 100⁺ 08090012

Dimensions		W295 X D295 X H385mm		
Weight		9kg/ 19.85lbs		
Electrical ratings		100-230V, 50-60Hz, 60W		
Protection class		I		
Ambient temperature		5-40°C (41-104°F)		
Sound level		<60 (65) dB (A)		
Relative humidity		max. 85%		
Compressed air		4-6 bar (58-87 ps)		
Air consumption		40 NL/min		
Compressed air quality	Residual oil content	max. 0.1 mg/m ³		
	Residual dust	max. 1 μ m; max. 1 mg/m ³		
	Residual water	max. $0.1 \text{ g/m}^3 \text{ at } -40^{\circ}\text{C (-}40^{\circ}\text{F)}$		

EASY TO USE

TTcare 100+ is designed to response to Dentists' requests. Its user-friendly interface simplifies the process of cleaning handpieces. It takes 15 sec only to lubricate and clean each handpiece, and less than one minute for three at a time. It's fast and time-saving to provide premium care for handpieces.

MINOR DETAILS MAKE BIG DIFFERENCES

In order to improve customer's using experience, TTcare 100+ includes the exceptional details: LCD screen, simply disassembled front door, exclusive chuck care system, easy spray can insertion and replacement, air driven motor design to highlight its functionality and features.

FEATURES

- Automatically cleans and maintains up to three handpieces
- Unique chuck care system
- Optional lubricant coverage throughout the handpiece
- Compressed-air connection: excess lubricant purging with special suction design
- Automated reproducible quality of care
- Easy spray can insertion and replacement
- Can coupling with unique safety valve
- Oil collecting drawer for excess lubricant
- LCD screen display
- Is capable to run without compressed air
- Maintain 1 handpiece in only 15 secs
- Unique drive motor design ensures the excellent clean process
- Quickly disassemble the front door and plain surface for easy clean process

32

EXCLUSIVE CHUCK CARE SYSTEM

- STEP 1 Place chuck into chuck care adapter.
- STEP 2 Press program button to start the processing.
- STEP 3 Clean and care handpiece's chuck.



Simply Disassemble

With thoughtful idea, it's effortless to keep TTcare 100+ in a good stage.

Simply disassemble the front door for further cleaning.





Amazed by fancy design

Compressed air purge excess lubricant into suction hole and oil collecting drawer, that makes inside of TTcare 100+ to stay clean.





TTlube Spray 08090011

Easy spray can insertion and replacement.



DONE IN A SIMPLE WAY

- STEP 1 Flip down the door and snap one, two or three handpieces onto the adapters.
- STEP 2 Close the door.
- STEP 3 By pressing the corresponding buttons to start the automated, internal cleaning and care of up to three handpieces.
- STEP 4 Finish and remove the handpieces.



FEATURES OF ACTIVE-LUB SYSTEM



- Optimizing the overall lubrication: The Active-lub system evenly distributes the lubricants to the inside of all components to lubricate contra-angle handpieces.
- Reliability and flexibility: Driving motor uses the belt to drive the operation smoothly, which brings out the features of quiet, stable, and vibration-free. The driven ports could be optionally increased or decreased based on the need.

(For contra-angle only)

HANDPIECE ADAPTOR AVAILABILITY

Image	Description	Product Code	Image	Description	Product Code
	Adapter KaVo	0PL0345		Adapter Star	0PL0413
	Adapter W&H	0PL0346		Adapter Midwest	0PL0551
	Adapter NSK	0PL0344		Adapter Midwest CA	0PL0583
مالآلات	Adapter Bien-Air	0PL0348		Adapter Borden	OPL0110
	Adapter SIRONA	0PL0347	\Diamond	Blister	0PL0350
0187116	Adapter E-type	0PL0349	· ·	Absorption pads(set)	0PL0351

34 35